In the Claims

The following listing of the claims replaces all previous listings.

1. (Currently Amended) A commanding system for a computer, comprising:

a memory storing an input module that accepts a plurality of input sequences across multiple input device categories, and a commanding element at an application level having a binding table that connects input to associated action, at least one binding entry in the binding table including sub-command bindings associated with the plurality of input sequences across multiple input device categories, and the memory further comprises a second commanding element at a control level or an operating system level having a second binding table that connects input to associated action, at least one binding entry in the second binding table including sub-command bindings associated with the plurality of input sequences across multiple input device categories; and

- a processor in data communication with the memory, the processor programmed to: receive the input at the input module;
 - pass the input to the commanding element at the application level, the commanding element looking up a matching sub-command binding associated with the input in the binding table;
 - invoke action connected with the input if the matching sub-command binding is found in the binding table;
 - tunnel the input to the second commanding element <u>at the control level or the</u>

 <u>operating system level</u>, the second commanding element looking up the
 matching sub-command binding associated with the input in the second
 binding table; and
 - invoke action connected with the input if the matching sub-command binding is found in the <u>binding table or the</u> second binding table.
- (Original) The system of claim 1, wherein at least two of the plurality of input sequences from the multiple input devices are selected from the group consisting of a keyboard, mouse, pen, and microphone.

- (Original) The system of claim 1, wherein the listing of the command bindings includes entries for a keyboard, a mouse, a pen, and a microphone.
- (Original) The system of claim 1, wherein the processor is further programmed to: traverse the binding table; and report a command associated with each binding entry of the binding table.

5.-11. (Canceled)

 (Previously Presented) A method for commanding a computer system, comprising: receiving one of a plurality of input sequences generated by different input device categories;

passing the input sequence to a commanding element;

looking up a matching binding entry associated with the input sequence in a binding table, the matching binding entry including a plurality of sub-command bindings for the different input devices;

invoking a handler associated the input if the matching binding is found in the binding table;

receiving a request to report commanding information; traversing the binding table; and reporting each command in each entry of the binding table.

- 13. (Original) The method of claim 12, wherein the different input device categories include at least two selected from the group consisting of a keyboard, a mouse, a pen, and a microphone.
- 14. (Original) The method of claim 12, wherein the different input device categories include a keyboard, a mouse, a pen, and a microphone.
- 15. (Canceled)
- 16. (Original) The method of claim 12, further comprising:

passing the input sequence to a second commanding element;

looking up the matching binding entry associated with the input sequence in a second binding table associated with the second commanding element, the matching binding entry including a plurality of sub-command bindings for the different input devices; and

invoking a handler associated the input if the matching binding is found in the second binding table.

17. (Canceled)